

**S15****Semi-Gloss Paper / Acrylic / White glassine****FACESTOCK**

Lightweight coated paper facestock. Smooth surface and semi-gloss finish.

Basis Weight: 53.9 lbs/ream  
Caliper: 0.0028 in

**ADHESIVE**

A general-purpose permanent water-based acrylic adhesive.

The adhesive is designed to provide good room temperature and semi-cold adhesion properties on a variety of surfaces. Not recommend on PVC.

This adhesive meets the requirements of FDA CFR 175.105 for indirect food contact.

**Typical Performance Data:**

Minimum Application Temperature: 2°C  
Service Temperature Range: -30°C to 80°C

Loop Tack (SS)-FTM9: 2.0 lbs / in  
180°Peel (SS)-FTM1: 3.8 lbs / in

**LINER**

A calendared white glassine paper with good roll label converting properties.

Basis Weight: 39.1 lbs/ream  
Caliper: 0.0019 in

**APPLICATIONS AND USE**

Suitable for consumer applications such as food, retail, beverage and health and beauty labelling.

**PRINTING/CONVERTING**

This product is suited for standard label printing technologies. Ink testing is recommended before production.

Excellent converting performances in rotary and flat-bed die-cutting.

**SHELF LIFE**

One year when stored at 23±2°C at 50±5% RH.

**STATEMENT OF PRACTICAL USE**

All materials, sales and contracts for sale of LabelEdge products are sold with the express requirement and understanding that the customer is solely and exclusively responsible for testing and for ensuring the products are fit for the customer's purposes or an end-user's purposes. All express or implied warranties of merchantability and fitness for particular use are disclaimed.